



Fabpro, Inc.

3000 E. Preston Street
Baltimore, MD 21213
Telephone (410) 325-5040

HAZARD RATING HMIS

Health=1, Flammability = 0, Reactivity= 0
(Index: 4=very high, 3=high, 2=moderate
1=slight, 0=insignificant)

Material Safety Data Sheet

I. General Information

Trade Name & Synonym Soot Sealer		Chemical Family Acrylic Emulsion
Chemical Name & Synonym Mixture	Date prepared August 1995	Prepared by Aziz Ullah Ph.D.

II. Ingredients

Water, Acrylic Emulsion, Solubilizing Aids

III. Physical Properties

Boiling Point

Approx. 212°F

Specific Gravity (Water=1)

1.02

Vapor Pressure (mm Hg.)

ND

Melting Point

Below 40°F

Vapor Density (AIR=1)

>1

Evaporation Rate (Butyl Acetate=1)

>1

Solubility in Water

Soluble

Appearance and odor

hazy liquid , acrylic odor

pH (Liquid as is)

6.0-8.0

IV. Fire and Explosion Hazard Data

Flash Point (TOC)

Over 200°F

Flammable Limits

NA

LEL

UEL

NA

Extinguishing Media

Foam, CO₂, Dry Chemical, Water Fog

Special Fire Fighting Procedures

Usual fire fighting procedures can be used

Unusual Fire and Explosion Hazards

None known

V. Reactivity Data

Stability

Unstable

Conditions to avoid

Stable

X

Incompatibility (Materials to avoid)

Acids, strong oxidizing agents

Hazard Decomposition or Byproducts

When exposed to fire emits normal products of combustion

Hazardous

May occur

Conditions to avoid

Polymerization

Will not occur

X

Fabpro, Inc.

Material Safety Data Sheet

VI. Health Hazard Data

Routes of Entry	Inhalation	Skin	Ingestion	Eyes
	Yes	No	Yes	Yes

Health Hazards

Direct contact of product with eyes can cause severe irritation; product can cause discomfort if taken internally

Signs and Symptoms of Exposure

Irritation discomfort

Medical Conditions Aggravated by Exposure

None known

Emergency and First Aid Procedures

Flush thoroughly with water. If irritation persists see physician, if ingested drink milk or water see physician

VII. Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Flush with water, (non-hazardous waste)

Waste Disposal Method

Check with federal state or local regulations. Waste may be discharged into sanitary sewer as non-hazardous waste if regulations permit

Precautions to be taken in Handling and Storing

Keep away from heat; keep away from eyes and repeated or prolonged contact with skin

Other Precautions

NA

VIII. Control Measures

Respiratory Protection

Respiratory Protection required when spraying product

Ventilation	Local Exhaust	Special
Not normally required		

Mechanical	Other

Protective Gloves

For repeated contact impermeable gloves suggested

Eye Protection

Monogoggles suggested

Other Protective Clothing or Equipment

NA

Work/Hygienic Practices

Wash after handling Keep out of reach of children

DISCLAIMER: Fabpro warrants this product conforms to specifications when used as directed No guarantee is made to the accuracy of any data or statement contained herein, as this information is furnished in good faith and believed to be true and accurate. No warranty, express or implied is made. This information is offered for consideration investigation and verification. Fabpro is not liable for incidental, special, or consequential damages with its publication.